

# Product Information

**Product:** New 6 lt. AFFF – slimline version

**Type:** 6 lt. AFFF stored pressure extinguisher

**Application:** Hospitals, Supermarkets, Hotels, and Restaurants, Paint shops, Fast Food chains, Clothing & Fabric industries, Industrial units, Offices etc.

**Features:**

- Slimline design (Ø 170mm diam.)
- Easy to handle
- Effective spray application
- Ergonomic design
- Replaces bulkier 9 lt. Water
- Higher performance



**Benefits:**

- Now available without torque
- Uses 1% AFFF
- Reduced service time
- Reliability
- Knockdown performance
- Ideal for offices

## Technical Data

Model	Capacity	Type	Weight of charged extinguisher	Extinguishing agent	Volume of extinguishing agent	Working pressure	Discharge Times	Range of jet horizontal	Temperature range	Height mm	Width mm	Depth mm
S6 DLWB	6 litre	Stored pressure	10.5kg	1% AFFF	6 litre	7 bar	>36 sec.	4-6m	-0°C to +60°C	455	260	170

**FOAM EXTINGUISHERS** are ideally suited where both class A & B fire risks exist. Aqueous Film Forming Foam or AFFF is particularly suited to fight liquid spill fires such as petrol, oil, fats, paints etc. and works by forming a film on the liquid to extinguish the fire. This extinguisher has also passed the electrical conductivity test at 35kv.



Model	A	B	C	D METAL
S6DLWB	13 A	183 B		

